



14 Fairlie Ave
Macleod Vic 3085
Australia

Phone:
+613 9444-8025

Fax:
+613 9435-1419

Email:
ian@jackaroo.net.au

Web:
www.jackaroo.net.au

ABN:
123456-789-12

D490 17" Widescreen Graphic Performance Laptop



Technical Specification

CPU	Intel Pentium® 4 2.80/ 3.00/ 3.20 GHz Processor, FSB800, 512Cache, 0.13µ core in uFC-PGA478 Package
Core Logic	SIS M648FX + 963 chipset
Display	ATI Mobility Radeon 9600 PRO high performance chip, Integrated 128-bit 2D / 3D Graphics Accelerator, Advanced HW Acceleration for DVD Playback, Fully DirectX 9 Support, 128MB DDR SGRAM on board, Dual-View Display Monitor, External Display resolution up to 1600x1200
Memory	Standard 256MB DDR RAM, Two 200Pins SODIMM sockets, support DDR333/ DDR400, Expandable memory up to 1024 MB, depends on 128/256/512MB SODIMM Module
BIOS	1x 512KB Flash ROM, Phoenix BIOS
LCD	17.0: WXGA TFT LCD
Storage	Bay-1 6-in-1 flash card reader Bay-2 Changeable 12.7mm (h) / DVD-RW /Combo drive One changeable 2.5" 9.5/12.7 mm (h) HDD Support Master Mode IDE, support PIO mode 4 / ATA-33/66/100/133 (Ultra DMA)
Audio	AC'97 2.2 Compliant Interface, 3D stereo enhanced sound system, Virtual 6-channel audio output, Compatible Sound-Blaster PRO, S/PDIF Digital output (5.1 CH), Built in microphone, Built in 4 speakers
Keyboard	Win Keys, Multi-Language, Full Size with Numeric PAD
PCMCIA	One PCMCIA 3.3V/ 5V sockets, one type II, Support Card Bus
Interface	Built in Touch pad (Scroll functionality included), 2x USB 2.0, 1x mini IEEE 1394, DC in jack, S-Video jack for TV output, 1x serial port, 1x parallel port, 1x IrDA, ix CRT output One PS/2 port support mouse and keyboard (through Y cable), 1x Headphone jack, 1x Microphone jack, 1x RJ-11 for Modem, 1x RJ-45 for LAN, Built-in 3 instant keys, www, email, and applications
Communication	Infrared transfer: 115.2K bps SIR/ 4M bps FIR, 1cm~1M operating distance, IrDA 1.1 compliant, 1000BASE-T (Gigabit) LAN on board (10 /100 BASE-T compatible), Video Camera module (Factory option device), Integrated V.90/ 56K MDC Modem (V.92 compliant)
Power	Full Range AC adapter – AC in 100~240V, 50~60Hz DC Output 20V, 6.0A, Main battery smart Li-Ion easy changeable
Indicators	LED Indicators (HDD, Suspend/ Power on/ AC-in, Battery Charging/ Battery Full, Num Lock, Caps, Scroll lock)
OS Support	Windows 2000/Windows XP-HOME (standard)/Windows XP Professional
Size	393 (W) x275 (D) x 37.5 (H) mm
Weight	3.85Kg without battery
Carry Bag	Free
Upgrade Options	Upgrade to 16x10x24x8DVD Combo Drive (CD-ROM+DVD-ROM+CD-RW) or DVD-RW Upgrade to 512MB or 1GB DDR RAM Upgrade to 40, 60 & 80GB HDD Upgrade to Windows XP Professional Add External USB 1.44 FDD Add Car Adaptor Microsoft Office 2003 Pro/ SBE/ Basic

* Note: Specifications are subject to change without prior notice.